

FIRE FIGHTING ROBOT EMBEDDED WITH GSM MODEM



Submitted By:

M.AbubakarMirza	111619050
ManzoorHussainArshad	111619042
Abdul Rehman	111619062
Irslan Ahmad	111619008

Supervised by: Ayesha Iqbal

**Department of Electrical Engineering
School of Engineering
University of Management and Technology, Lahore
June 2016**

FIRE FIGHTING ROBOT EMBEDDED WITH GSM MODEM

Submitted to the faculty of the Electrical Engineering Department of University of Management and Technology Lahore in partial fulfillment of the requirements for the Degree of

Bachelor of Science
in
Electrical Engineering

Project Advisor

Director Projects

Department of Electrical Engineering
School of Engineering
University of Management and Technology, Lahore

In The Name of Allah, The Most Beneficent, The Most Merciful

DECLARATION

We declare that the work contained in this report is our own, except where explicitly stated otherwise. In addition, this work has not been submitted to obtain another degree or professional qualification.

Signed:

Date:

ACKNOWLEDGEMENT

We would like to express our sincere gratitude to our project advisor Miss Ayesha Iqbal (Lecturer, EED, School of Engineering, UMT) for giving us the opportunity to work on the project “FIRE FIGHTING ROBOT EMBEDDED WITH GSM MODEM”.

Thanks are due to our university to introducing the major project. Also we would like to thank the University for believing in us that we can complete this project successfully.

Thanks are due to our project director “Sir Jameel Ahmad” for providing the student this platform to present such reports while pursuing their graduations.

We would like to extend our thanks to other faculty members of Electrical Engineering Department, who helped us in some or the other way in making our project.

At last thanks are due for the researchers whose paper gave us the right direction to work.

Dedication

To our beloved parents whose prayers made us able to walk through every step of life and without whose endless affections and encouragement we couldn't do anything.

TABLE OF CONTENTS

LIST OF FIGURES

LIST OF TABLES

ABSTRACT

1 INTRODUCTION

1.1 General	1
1.2 Problem Statement	2
1.3 Objectives of Study	2
1.4 Scope of study	2
1.5 Significance of Research	3
1.6 Thesis Organization	3

2 LITERATURE REVIEW 5

3 SYSTEM IMPLEMENTATION

3.1 Stepper Motors and Stepper Driver Circuit	8
3.2 Infrared Sensing Elements and Sensor Circuits	10
3.3 Microcontroller	11
3.4 Electrical Components	11
3.5 Features of the Fire Sensing and Extinguishing Robot	11
3.6 Programming Algorithm	12
3.7 Fire sensors	12
3.8 GSM Modem	12
3.9 Driver Circuit	12
3.10 DC Motors	13
3.11 Chassis	13
3.12 Working	13
3.13 Block Diagram	14

3.14	Circuit Diagram	15
3.15	Algorithms for Robot Control	16
3.16	Advantages & Disadvantages	17
4	CONCLUSION AND FUTURE SCOPE	
4.1	Conclusion	18
4.2	Future Scope	18
	References	19
	Appendix	20

LIST OF FIGURES

Figure 3.1: Internal Diagram of 4 Phase Stepper Motor	9
Figure 3.2: Phototransistor Sensor Voltage (V_{ce}) vs. Wall Distance	11
Figure 3.3: Block Diagram	14
Figure 3.4: Circuit Diagram	15
Figure 3.5: Program Flowchart Showing Overview of Robot Operations	16
Figure 3.6: Flowchart Wall-Following Algorithm	17

LIST OF TABLES

Table 3.1: Typical Stepping Sequence of a Four Phase Stepper Motor

8

Abstract

We want to develop associate intelligent multi detector based mostly fireplace fighting automaton in our existence.

Data for this study were gathered from different resources with the help of research papers. For boosting dc voltage from one level to other boost converter was used. This thesis is proposed to with provide a method of boosting dc voltage from 5 Volts to 14 Volts, by using a boost converter designed specifically for this task. Then this 12V DC is converted into same level Ac voltage using inverter. After that centered taped transformer increases 12V AC into 220V AC.

But at the same time power quality is also improved by LC filter

In conclusion, all aims, tests and data have been documented within this report. Results of simulation proved that the boost converter will increase 5 volts to 14 volts with 92% power conversion efficiency. Furthermore, Ac voltage obtained is obtained as an output of inverter.

